


Item
1312

1. Product description:

Seamless impregnated fiber wheel with shank

Dimensions (in):	4" x 1" x 1/4"
Dimensions (mm):	100 x 25 x 6.4
Material:	Aluminum Oxide
Specification:	A MED Rojo W I
Max. rpm:	6,900
Grit:	Medium
Optimal RPM:	1,900



D = 100 mm
T = 25 mm
S = 6.4 mm



Metal



Stainless



Non-ferrous
metals



1. Application

- For excellent polishing and finishing of bronze, copper, brass, stainless steel, and carbon steel parts.
- Seamless construction prevents marks on the overlap of polished surfaces.
- The impregnated fiber provides longer service life.
- Excellent for working on aluminum.
- Ideal for wide surfaces, tubes, and circular cavities.
- Leaves a continuous satin finish.

2. Operating instructions

- Can be used wet or dry.
- For use with a rotary tool or drill.
- Mount the wheel and let it run idle for one minute to verify that it is not damaged.
- Do not apply excessive pressure or strike the workpiece.

3. Safety information

- Never exceed the maximum speed indicated on the label.
- Always use safety guards.
- Always wear complete personal protective equipment (gloves, hearing protection, mask, and safety glasses).
- Improper use may cause serious injury.



Rotatory Tool
Die Grinder



Drill

4. Handling

- The initial inspection must be carried out in the original box. If there is visible evidence of damage to the packaging, the product should not be accepted.
- Handle the wheels carefully to prevent tearing or cracking. If a product breaks, loses a section, or shows signs of damage, it must not be mounted.

5. Storage

- Store the product on a flat surface at least 10 cm (4 in) above the ground, away from damp, cold, or hot surfaces, or any type of fluid.
- The ideal storage conditions for these products are 40–50% relative humidity and a temperature between 15 °C and 29 °C (59 °F and 84 °F).

6. Packaging units

- 1 piece.