




Item  
**2127**

## 1. Product description:


Segmented diamond blade

<b>Dimensions (in):</b>	14" x 0.125" x SC
<b>Dimensions (mm):</b>	350 x 3.2 x SC
<b>Segment height:</b>	10 mm
<b>Specification:</b>	PLATINO 4000 M*
<b>Max. rpm:</b>	4,400
<b>Line:</b>	Platino 4000



**DDD**

**D = 350 mm**  
**T = 3.2 mm**  
**H = SC**  
**W = 12 mm**



## 1. Application

- For cutting green concrete and asphalt.
- Segments feature aligned and alternating diamond placement.
- Special bore design for green concrete cutting machines with medium aggregate materials.

## 2. Operating instructions

- For wet use.
- Use with a floor saw.
- Mount the blade following the direction of rotation indicated by the arrow on the blade and let it spin idle for one minute to verify it is not damaged.
- Use moderate feed speed and cutting depth, as excessive pressure can damage the diamonds.

## 3. Safety information

- Always use safety guards.
- Never exceed the maximum operating speed indicated on the label.
- Always wear full personal protective equipment (gloves, hearing protection, mask, and safety glasses).
- Do not use for grinding operations.
- Never attempt curved cuts.



Floor Saw

## 4. Handling

- The initial inspection must be carried out while the product is still in its original packaging. If there is any visible evidence of damage, the product should not be accepted.
- Handle blades carefully to avoid impacts or drops. If a blade shows cracks, broken segments, or visible damage, it must not be mounted.

## 5. Storage

- The blade should be stored in conditions free from moisture, dust, and dirt — preferably in its original packaging — and should not be exposed for long periods to hot, cold, or wet surfaces.

## 6. Packaging units

- 1 piece.