# Data Sheet

Item
# 3007

## 1. Product description:

Sandpaper Sheet

| | |
|---|---|
| **Dimensions (in):** | 9" x 11" |
| **Dimensions (mm):** | 230 x 280 |
| **Specification:** | AASA-220 |
| **Grit:** | 220 |
| **Abrasive:** | Aluminum Oxide |
| **Backing:** | A-weight Waterproof Paper |
| **Structure:** | Semi-Open Coat |





**HL**




**A = 230 mm**
**L = 280 mm**







Made in Germany

Individually Barcoded



Manual Use

## 1. Application

• For sanding paint, body filler, primer, ferrous and non-ferrous metals, plastics, wood, and textiles.
• Extra-high performance with excellent stock removal capacity.
• Tear-resistant, clog-resistant, and minimizes abrasive grain shedding.
• Ideal for automotive refinishing applications.
• Excellent flexibility makes them ideal for contoured and irregularly shaped workpieces.
• Provides a uniform surface finish.

## 2. Operating instructions

• For hand sanding applications.
• Use with plenty of water during sanding. After use, soak the abrasive sheet in water to help restore its cutting action.

## 3. Safety information

• Always wear full personal protective equipment (gloves, hearing protection, mask/respirator, and safety goggles).
• Improper use may cause injury.

## 4. Handling

• Initial inspection must be carried out in the original packaging. If there is visible damage to the packaging, the product should not be accepted.
• Packages must not be exposed to hooks or sharp objects. They should not be stacked under excessive loads, as this may damage the product and cause breakage during use.

## 5. Storage

• All sanding products must be stored on pallets at least 10 cm above the floor, away from damp, cold, hot surfaces, or any type of fluid.
• Ideal storage conditions are 40–50% relative humidity and a temperature between 15 and 29 °C.

## 6. Packaging units

• 50 pieces.