

Item
3113


1. Descripción del producto:

Sanding Disc with **ULTRAGRIP®** backing system

Dimensions (in):	6"
Dimensions (mm):	152
Abrasive:	Ceramic Aluminum Oxide
Grit:	40
Specification:	TCGB-40
Backing:	"C" Paper
Structure:	Open Coat



DL UGA



D = 152 mm



1. Application

- High sanding power on wood, metal, paint, and plastic.
- Ideal for woodworking, automotive repair, painting, and industrial applications.
- Characterized by fast cutting and long service life.
- Consistent results and excellent finishes, as its technology reduces the risk of clogging.

2. Operating instructions

- Use with a random orbital sander.
- Mount the disc onto the appropriate backing pad according to the attachment system.
- Install the disc and let it run idle for one minute to ensure it is not damaged.
- Do not apply excessive pressure or strike the work surface.

3. Safety information

- Never exceed the maximum speed indicated on the label.
- Always use full personal protective equipment (gloves, hearing protection, mask, and safety glasses).
- Improper use may cause serious injury.



4. Handling

- Initial inspection must be carried out in the original packaging. If there is visible damage to the packaging, the product should not be accepted.
- Packages must not be exposed to hooks or sharp objects. They should not be stacked under excessive loads, as this may damage the product and cause breakage during use.

5. Storage

- All sanding products must be stored on pallets at least 10 cm above the floor, away from damp, cold, hot surfaces, or any type of fluid.
- Ideal storage conditions are 40–50% relative humidity and a temperature between 15 and 29 °C.

6. Packaging units

- 25 pieces.