

Item  
**3121**


## 1. Descripción del producto:

Sanding Disc with **ULTRAGRIP®** backing system

<b>Dimensions (in):</b>	6"
<b>Dimensions (mm):</b>	152
<b>Abrasive:</b>	Ceramic Aluminum Oxide
<b>Grit:</b>	240
<b>Specification:</b>	TCGB-240
<b>Backing:</b>	"C" Paper
<b>Structure:</b>	Open Coat



**DL UGA**



**D = 152 mm**



## 1. Application

- High sanding power on wood, metal, paint, and plastic.
- Ideal for woodworking, automotive repair, painting, and industrial applications.
- Characterized by fast cutting and long service life.
- Consistent results and excellent finishes, as its technology reduces the risk of clogging.

## 2. Operating instructions

- Use with a random orbital sander.
- Mount the disc onto the appropriate backing pad according to the attachment system.
- Install the disc and let it run idle for one minute to ensure it is not damaged.
- Do not apply excessive pressure or strike the work surface.

## 3. Safety information

- Never exceed the maximum speed indicated on the label.
- Always use full personal protective equipment (gloves, hearing protection, mask, and safety glasses).
- Improper use may cause serious injury.



## 4. Handling

- Initial inspection must be carried out in the original packaging. If there is visible damage to the packaging, the product should not be accepted.
- Packages must not be exposed to hooks or sharp objects. They should not be stacked under excessive loads, as this may damage the product and cause breakage during use.

## 5. Storage

- All sanding products must be stored on pallets at least 10 cm above the floor, away from damp, cold, hot surfaces, or any type of fluid.
- Ideal storage conditions are 40–50% relative humidity and a temperature between 15 and 29 °C.

## 6. Packaging units

- 50 pieces.