

Item 4262


1. Product description:

Cut-Off Wheel for Stainless Steel

| | |
|-------------------------|------------------------|
| Dimensions (in): | 4-1/2" x 0.040" x 7/8" |
| Dimensions (mm): | 115 x 1 x 22.23 |
| Abrasive: | Aluminum Oxide |
| Specification: | A60R-BFP |
| Max. rpm: | 13,300 |
| Line: | Tyrolit |
| Max. speed: | 80 m/s |



Type 41



| | | |
|------------|--------------|-----------|
| D = | 115 | mm |
| T = | 1 | mm |
| H = | 22.23 | mm |



Stainless

Certification

This wheel is certified by the Organization for the Safety of Abrasives.



1. Application

- Ultra-thin cut-off wheel for working on stainless steel, sheets, reinforced steel, profiles, and thin-walled pipes.
- Long service life and excellent cutting speed, delivering up to 40% higher performance than conventional wheels.
- Designed to reduce noise and vibration, providing a smoother and safer cutting experience.
- Specialized for users requiring high-productivity performance wheels.

2. Operating instructions

- For use on an angle grinder.
- Mount the wheel and let it run idle for one minute to verify that it is not damaged.
- Keep the wheel positioned at 90° to the work surface.
- Do not apply excessive pressure or strike the workpiece.

3. Safety information

- Before mounting or removing the wheel, make sure the machine is disconnected.
- Never exceed the maximum speed indicated on the label.
- Always use safety guards.
- Always wear complete personal protective equipment (gloves, hearing protection, mask, and safety glasses).
- Never attempt curved cuts.



- Never use a wheel that has become wet.
- Do not use for grinding operations.
- Improper use may cause serious injury.
- Use only as specified in ANSI B7.1.

4. Handling

- The initial inspection must be carried out in the original box. If there is visible evidence of damage to the packaging, the merchandise should not be accepted.
- Handle the wheels carefully to prevent impact or drops. If a wheel is dropped, cracked, loses a section, or shows any sign of damage, it must not be mounted.

5. Storage

- Store wheels on a flat surface; do not hit or drop them.
- Wheels must not be exposed to:
 - (a) Water or other solvents.
 - (b) Extreme temperatures or humidity conditions.
- For more information, consult ANSI B7.1.

6. Packaging units

- 25 pieces.